

EXTERIOR GUTTER



EXTERIOR GUTTER D110WITH A ZINC-PLATED/PLASTIC GRID

The gutter series CH 900and CH 900M are made of UV-stabilised PP and supplied in two options. Loading capacity compliant to EN 1433-A-15. Designed for areas used by pedestrians and cyclists, as well as for driveways, etc.

PART Nr. NAME	PACKAGING [pcs/pallet]	WEIGHT [kg/pcs]	LOAD CAPACITY
------------------	---------------------------	--------------------	------------------



CH 900 Zinc plated grid	1/100	2,00	1 500 kg
--------------------------------------	-------	------	----------

CH 900 M Plastic grid	1/100	1,60	300 kg
---------------------------------	-------	------	--------

EXTERIOR GUTTER D110WITH WITH ZINC-PLATED/CAST IRON GRID

The exterior gutter CH 1001with a cast iron grid is suitable for draining water from construction sites, areas used by pedestrians and cyclists, as well as for driveways, pathways, parking lots etc. Loading capacity B (testing force 125kN). Made from HD-PE, UV stabilized, and from grey cast iron DIN 1691. Loading capacity compliant to EN 1433-B125(12, 500kg).

PART Nr. NAME	PACKAGING [pcs/pallet]	WEIGHT [kg/pcs]	LOAD CAPACITY
------------------	---------------------------	--------------------	------------------



CH 1000 Zinc plated grid	1/54	2,73	1 500 kg
---------------------------------------	------	------	----------

CH 1001 Cast iron grid	1/54	7,50	12 500 kg
----------------------------------	------	------	-----------

ACCESSORIES



CH 1003 Side connecting set DN110	-	-	-
--	---	---	---



CH 1004 Bottom connec- ting set DN110	-	-	-
--	---	---	---



CH 1005 Cross transition piece	-	-	-
---	---	---	---

